


Microphone Cable SC-Galileo 238; 2 x 0,38 mm²; PVC Ø 7,00 mm; black

Art. No.: 200-0251

ANALOG

OFC



General Data

Article number :	200-0251
Name :	SC-Galileo 238
EAN :	4049371001212
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application :	Microphone Cable
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,38mm ²)YDDY
Jacket material :	PVC
Jacket Ø [mm] :	7,00
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,38
Inner conductor Ø (audio) [mm] :	0,70
AWG (audio) :	21
Shielding :	Double copper spiral, counter-rotating
Shielding factor [%] :	100
Copper strands (audio) :	48
Copper strand Ø (audio) [mm] :	0,10
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,55
Weight per 1 m [g] :	60
UV-resistant :	yes
Fire load per m [kWh] :	0,22
Style variant :	round
Packing :	100 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	7
Height [mm] :	7

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	50
Capac. cond./shield. per 1 m (audio) [pF] :	100

Impedance [Ω] :	38
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	52
Shield. resistance per 1 km [Ω] :	20