

# SC-Monocat 110C; power: 3 x 2,50 mm<sup>2</sup>x CAT.7; PVC Ø 13,80 mm; black

Art. No.: 500-0151-1

**ANALOG**   **DIGITAL**   **OFC**



## General Data

Article number :	500-0151-1
Name :	SC-Monocat 110C
EAN :	4049371050975
Properties :	Analog
Properties :	OFC oxygen free copper
Properties :	Digital 110 Ω AES / EBU
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application :	hybrid cable
Colour :	black
BPVo-Euroclass :	Fca

## Technical Data

Construction :	[(3LIY3x2,5mm <sup>2</sup> )Y+1x(4x(2LI2Yx0,14mm <sup>2</sup> ))(ST)CY]Y
Construction (power) :	[(3LIY3x2,5mm <sup>2</sup> )Y
Construction (network) :	1x(4x(2LI2Yx0,14mm <sup>2</sup> ))(ST)CY]Y
Jacket material :	PVC
Jacket Ø [mm] :	13,80
Inner conductor (power) :	3
Inner conductor (network) :	8
Inner conductor (power) [mm <sup>2</sup> ] :	2,50
Inner conductor (network) [mm <sup>2</sup> ] :	0,14
Shielding (network) :	AL / PT-foil + Copper braiding tin-plated
Shielding factor [%] :	100
Copper strands (network) :	7
Copper strand Ø (network) [mm] :	0,16
Conductor insulation material :	Foam / Skin-PE
Weight per 1 m [g] :	254
UV-resistant :	yes
Fire load per m [kWh] :	1,1
Style variant :	round
Packing :	bulk stock
CAT-Type :	CAT.7
Max. section length [m] :	100
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	13,8
Height [mm] :	13,8

## Electrical Data

Capacity wire/wire at 1m (network) [pF] :	44
Impedance (network) [Ω] :	100
Insulation resist. per 1km (power) [GΩ] :	5
Test voltage [V] :	2000
Nominal voltage (power) [V] :	500
Operating voltage (power) [V] :	300