


## RG/U Coax SC-Classic Series MKII; 1 x 1,06; PVC Ø 10,30 mm; black Art. No.: 600-0471

**ANALOG** **DIGITAL** **OFC**



### General Data

Article number :	600-0471
Name :	SC-Classic Series MKII
EAN :	4049371005777
Properties :	Analog
Properties :	OFC oxygen free copper
Properties :	Digital 75 Ω
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	RG/U Coax
Colour :	black
BPVo-Euroclass :	Fca

Damping at 100 MHz (100m & 20° C) [dB] :	7,7
Damping at 200 MHz (100m & 20° C) [dB] :	11,2
Damping at 470 MHz (100m & 20° C) [dB] :	17,3
Damping at 862 MHz (100m & 20° C) [dB] :	25,5
Damping at 1000 MHz (100m & 20° C) [dB] :	27,7
Impedance [Ω] :	75

### Technical Data

Construction :	02YSCY
Jacket material :	PVC
Jacket Ø [mm] :	10,30
Number of Channels (video) :	1
Inner conductor (video) :	1
Inner conductor (video) [mm <sup>2</sup> ] :	0,88
Inner conductor Ø (video) [mm] :	1,06
AWG (video) :	18
Shielding :	Copper braiding, bare
Shielding factor [%] :	92
Copper strands (video) :	7
Copper strand Ø (video) [mm] :	0,40
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	7,30
Weight per 1 m [g] :	127
UV-resistant :	yes
Fire load per m [kWh] :	0,73
Style variant :	round
Packing :	100 m ring
Packing :	500 m spool
Velocity factor :	0,66
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
RG-Type :	RG11A/U
Width [mm] :	10,3
[mm] :	10,3

### Electrical Data

Capacity wire/electic screen at 1m (video) [pF] : 67