


## video cable SC-Focusline LC CPR-Version; 1 x 0,60; PVC Ø 6,20 mm; black; Eca

Art. No.: 600-0051LC

**ANALOG** ~~Das~~ **OFC** ~~Das~~



### General Data

Article number :	600-0051LC
Name :	SC-Focusline LC CPR-Version
EAN :	4049371385459
Properties :	Digital 75 Ω
Properties :	OFC oxygen free copper
Properties :	Analog
Application area :	ELA 100 V
Application area :	Installation
Application area :	Studio / Broadcast
Application area :	Mobile outdoor / indoor
Application :	video cable
Colour :	black
BPVo-Euroclass :	Eca

### Technical Data

Construction :	02YS(ST)CH0,6/3,7
Jacket material :	PVC
Jacket Ø [mm] :	6,20
Number of Channels (video) :	1
Inner conductor (video) :	1
Inner conductor (video) [mm²] :	0,22
Inner conductor Ø (video) [mm] :	0,60
AWG (video) :	23
Shielding :	Copper braiding
Shielding factor [%] :	92
Copper strands (video) :	7
Copper strand Ø (video) [mm] :	0,20
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	3,70
Weight per 1 m [g] :	44
UV-resistant :	yes
Fire load per m [kWh] :	0,23
Style variant :	round
Packing :	1000 m spool
Packing :	100 m spool
Velocity factor :	0,66
Temperature min. [°C] :	-20
Temperature max. [°C] :	70
Width [mm] :	6,2
Height [mm] :	6,2

### Electrical Data

Capacity wire/electic screen at 1m (video) [pF] : 67

Damping at 5 MHz (100m & 20° C) [dB] :	2,5
Damping at 50 MHz (100m & 20° C) [dB] :	6,2
Damping at 100 MHz (100m & 20° C) [dB] :	10,2
Damping at 200 MHz (100m & 20° C) [dB] :	13,1
Impedance [Ω] :	75
Conductor resistance per 1 km [Ω] :	150
Shield. resistance per 1 km [Ω] :	13