


SC-AQUA MARINEX ARAMID MIKRO14; 2 x 0.14 mm²; PUR-SR with ARAMID reinforcement Ø 6,20 mm

Art. No.: **200-0131AQ**



General Data

Article number :	200-0131AQ
Name :	SC-AQUA MARINEX ARAMID MIKRO14
EAN :	4049371480222

Technical Data

Jacket material :	PUR-SR with ARAMID reinforcement
Jacket Ø [mm] :	6,20
Inner conductor (AES/EBU, DMX) :	2
Inner conductor (AES/EBU, DMX) [mm ²] :	0,14
Shielding :	Copper spiral + special protective bandage
Shielding factor [%] :	95
Copper strands (AES/EBU, DMX) :	18
Copper strand Ø (AES/EBU, DMX) [mm] :	0,10
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,20
Weight per 1 m [g] :	55
Fire load per m [kWh] :	0,22
Packing :	100 m spool
Temperature min. [°C] :	-40
Temperature max. [°C] :	80
Max. water depth [m] :	20
Max. water pressure [bar] :	2

Electrical Data

Capac. cond./cond. per 1 m (AES/EBU, DMX) [pF] :	45
Capac. cond./shield. per 1 m (AES/EBU, DMX) [pF] :	90
Impedance [Ω] :	110
Insulation resist. per 1 km [GΩ] :	1
Conductor resistance per 1 km [Ω] :	140
Shield. resistance per 1 km [Ω] :	10