

## Patch cable SC-Isopod SO-F22; 2 x 0,22 mm<sup>2</sup>; FRNC Ø 3,30 mm; black Art. No.: 200-0401F

ANALOG

FRNC

OFC



### General Data

Article number :	200-0401F
Name :	SC-Isopod SO-F22
EAN :	4049371004497
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Installation
Application :	Patch cable
Colour :	black
BPVo-Euroclass :	Fca

### Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,22mm <sup>2</sup> )(ST)Y
Jacket material :	FRNC
Jacket Ø [mm] :	3,30
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm <sup>2</sup> ] :	0,22
Inner conductor Ø (audio) [mm] :	0,53
AWG (audio) :	24
Shielding :	AL / PT foil + AL / PT foil + filler strand, tin-plated
Shielding factor [%] :	100
Copper strands (audio) :	7
Copper strand Ø (audio) [mm] :	0,20
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,12
Weight per 1 m [g] :	16
UV-resistant :	yes
Fire load per m [kWh] :	0,05
Style variant :	round
Packing :	200 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	3,3
Height [mm] :	3,3

### Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	74
Capac. cond./shield. per 1 m (audio) [pF] :	143
Insulation resist. per 1 km [GΩ] :	0,2
Insulation resist. per 1 km (audio) [GΩ] :	0,2
Conductor resistance per 1 km [Ω] :	88

Shield. resistance per 1 km [Ω] :

75