

SC-AQUA MARINEX BINARY 422; 4 x 0.22 mm²; PUR-SR Ø 7,00 mm

Art. No.: 550-0241AQ



General Data

Article number :	550-0241AQ
Name :	SC-AQUA MARINEX BINARY 422
EAN :	4049371481816

Technical Data

Jacket material :	PUR-SR
Jacket Ø [mm] :	7,00
Inner conductor (AES/EBU, DMX) :	4
Inner conductor (AES/EBU, DMX) [mm ²] :	0,22
Shielding :	Copper braiding, tin-plated + AL / PT-foil + special protective banding
Shielding factor [%] :	100
Copper strands (AES/EBU, DMX) :	28
Copper strand Ø (AES/EBU, DMX) [mm] :	0,10
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,60
Weight per 1 m [g] :	75
Fire load per m [kWh] :	0,23
Packing :	Bulk Cable
Temperature min. [°C] :	-40
Temperature max. [°C] :	80
Max. water depth [m] :	50
Max. water pressure [bar] :	5

Electrical Data

Capac. cond./cond. per 1 m (AES/EBU, DMX) [pF] :	40
Capac. cond./shield. per 1 m (AES/EBU, DMX) [pF] :	108
Impedance [Ω] :	110
Insulation resist. per 1 km [GΩ] :	1
Conductor resistance per 1 km [Ω] :	90
Shield. resistance per 1 km [Ω] :	4,5