

Power Lead SC-AQUA MARINEX POWER 325; 3 x 2,50 mm²; PUR-SR, Ø 9,40 mm; black

Art. No.: 700-0241-0325AQ

ANALOG **AQUA** **OFC** **PUR**



General Data

Article number :	700-0241-0325AQ
Name :	SC-AQUA MARINEX POWER 325
EAN :	4049371194488
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	PUR
Properties :	Underwater / submerged
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Installation
Application area :	ELA 100 V
Application :	Power Lead
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Construction (power) :	(3LIY2,5mm ²)PU
Jacket material :	PUR-SR
Jacket Ø [mm] :	9,40
Number of Channels (power) :	1
Inner conductor (power) :	3
Inner conductor (power) [mm ²] :	2,50
AWG (power) :	13
Copper strands (power) :	140
Copper strand Ø (power) [mm] :	0,15
Conductor insulation material :	PUR
Weight per 1 m [g] :	147
UV-resistant :	yes
Fire load per m [kWh] :	0,48
Style variant :	round
Temperature min. [°C] :	-40
Temperature max. [°C] :	80
Width [mm] :	9,4
Height [mm] :	9,4

Electrical Data

Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1km (power) [GΩ] :	1
Test voltage [V] :	3000
Nominal voltage (power) [V] :	1000
Operating voltage (power) [V] :	1000