

video cable Cinema-SV; 2 x 0,32; PVC Ø 7,50 mm; black

Art. No.: 600-0701



General Data

Article number :	600-0701
Name :	Cinema-SV
EAN :	4049371000581
Properties :	Analog
Properties :	Digital 75 Ω
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application :	video cable
Colour :	black
BPVo-Euroclass :	Fca

Damping at 200 MHz (100m & 20° C) [dB] :	30,6
--	------

Damping at 470 MHz (100m & 20° C) [dB] :	60,5
--	------

Damping at 1485 MHz (100m & 20° C) [dB] :	92,3
---	------

Impedance [Ω] :	75
-----------------	----

Technical Data

Construction :	[2LI2Y0,32mm(ST)CY]Y
Jacket material :	PVC
Jacket Ø [mm] :	7,50
Number of Channels (video) :	2
Inner conductor (video) :	1
Inner conductor (video) [mm ²] :	0,08
Inner conductor Ø (video) [mm] :	0,32
AWG (video) :	28
Shielding :	Copper braiding tin-plated + AL-compound foil
Shielding factor [%] :	100
Copper strands (video) :	7
Copper strand Ø (video) [mm] :	0,12
Conductor insulation material :	Foam / Skin-PE
Conductor insulation Ø [mm] :	1,60
Weight per 1 m [g] :	68
UV-resistant :	yes
Fire load per m [kWh] :	0,36
Style variant :	round
Packing :	200 m spool
Temperature min. [°C] :	-15
Temperature max. [°C] :	70
Width [mm] :	7,5
Height [mm] :	7,5

Electrical Data

Capacity wire/electic screen at 1m (video) [pF] :	64
Damping at 5 MHz (100m & 20° C) [dB] :	4,3
Damping at 50 MHz (100m & 20° C) [dB] :	16,6
Damping at 100 MHz (100m & 20° C) [dB] :	22,5