

Microphone Cable SC-Silver Stage; 2 x 0,22 mm²; Soft PVC Ø 6,40 mm; black

Art. No.: 200-0011

ANALOG

DIGITAL

OFC



General Data

| | |
|--------------------|-------------------------------------|
| Article number : | 200-0011 |
| Name : | SC-Silver Stage |
| EAN : | 4049371422260 |
| Properties : | Ultrapure OFC copper, silver-plated |
| Properties : | Analog |
| Application area : | Installation |
| Application area : | Mobile outdoor / indoor |
| Application area : | Stage / live |
| Application : | Microphone Cable |
| Colour : | black |
| BPVo-Euroclass : | Fca |

Technical Data

| | |
|--|-------------------------------|
| Signal transmission : | symmetrical |
| Construction : | (2LI2Y0,22mm ²)DY |
| Jacket material : | Soft PVC |
| Jacket Ø [mm] : | 6,40 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 2 |
| Inner conductor (audio) [mm ²] : | 0,22 |
| Inner conductor Ø (audio) [mm] : | 0,53 |
| AWG (audio) : | 24 |
| Shielding : | Copper spiral shielding |
| Shielding factor [%] : | 99 |
| Copper strands (audio) : | 28 |
| Copper strand Ø (audio) [mm] : | 0,10 |
| Conductor insulation material : | Foam PE |
| Conductor insulation Ø [mm] : | 1,60 |
| Weight per 1 m [g] : | 54.6 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 0,22 |
| Style variant : | round |
| Packing : | 500 m spool |
| Packing : | 100 m spool |
| Temperature min. [°C] : | -20 |
| Temperature max. [°C] : | 60 |
| Width [mm] : | 6,4 |
| Height [mm] : | 6,4 |

Electrical Data

| | |
|---|-----|
| Capac. cond./cond. per 1 m (audio) [pF] : | 53 |
| Capac. cond./shield. per 1 m (audio) [pF] : | 103 |

| | |
|--|------|
| Impedance [Ω] : | 123 |
| Insulation resist. per 1 km [GΩ] : | 1 |
| Insulation resist. per 1 km (audio) [GΩ] : | 1 |
| Conductor resistance per 1 km [Ω] : | 42 |
| Shield. resistance per 1 km [Ω] : | 17,6 |