


Microphone Cable Stage 22 Highflex; 2 x 0,22 mm²; PVC Ø 6,40 mm; black

Art. No.: 200-0001

ANALOG

OFC



General Data

| | |
|--------------------|-------------------------|
| Article number : | 200-0001 |
| Name : | Stage 22 Highflex |
| EAN : | 4049371001830 |
| Properties : | Analog |
| Properties : | OFC oxygen free copper |
| Application area : | Stage / live |
| Application area : | Mobile outdoor / indoor |
| Application area : | Installation |
| Application : | Microphone Cable |
| Colour : | black |
| BPVo-Euroclass : | Fca |

Technical Data

| | |
|--|---|
| Signal transmission : | symmetrical |
| Construction : | (2LI2Y0,22mm ²)DY |
| Jacket material : | PVC |
| Jacket Ø [mm] : | 6,40 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 2 |
| Inner conductor (audio) [mm ²] : | 0,22 |
| Inner conductor Ø (audio) [mm] : | 0,53 |
| AWG (audio) : | 24 |
| Shielding : | Copper spiral shielding with 0.10 mm indiv. strands |
| Shielding factor [%] : | 99 |
| Copper strands (audio) : | 28 |
| Copper strand Ø (audio) [mm] : | 0,10 |
| Weight per 1 m [g] : | 47 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 0,22 |
| Style variant : | round |
| Packing : | 100 m spool |
| Packing : | 500 m spool |
| Temperature min. [°C] : | -20 |
| Temperature max. [°C] : | 70 |
| Width [mm] : | 6,4 |
| Height [mm] : | 6,4 |

Electrical Data

| | |
|---|-----|
| Capac. cond./cond. per 1 m (audio) [pF] : | 68 |
| Capac. cond./shield. per 1 m (audio) [pF] : | 130 |
| Impedance [Ω] : | 100 |
| Insulation resist. per 1 km [GΩ] : | 1 |

| | |
|--|----|
| Insulation resist. per 1 km (audio) [GΩ] : | 1 |
| Conductor resistance per 1 km [Ω] : | 87 |
| Shield. resistance per 1 km [Ω] : | 30 |