

Speaker Cable Elephant SPM425 CPR; 4 x 2,50 mm²; FRNC Ø 9,00 mm; black; Cca

Art. No.: 490-0051-425FC

ANALOG FRNC HALOGEN-FREE OFC



General Data

| | |
|--------------------|-------------------------|
| Article number : | 490-0051-425FC |
| Name : | Elephant SPM425 CPR |
| EAN : | 4049371411080 |
| Properties : | Halogen-free / LSZH |
| Properties : | FRNC flame retardant |
| Properties : | OFC oxygen free copper |
| Properties : | Analog |
| Application area : | ELA 100 V |
| Application area : | Installation |
| Application area : | Studio / Broadcast |
| Application area : | Mobile outdoor / indoor |
| Application area : | Stage / live |
| Application : | Speaker Cable |
| Colour : | black |
| BPVo-Euroclass : | Cca |

Technical Data

| | |
|--|----------------------------|
| Construction : | (4LIY2,5mm ²)Y |
| Jacket material : | FRNC |
| Jacket Ø [mm] : | 9,00 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 4 |
| Inner conductor (audio) [mm ²] : | 2,50 |
| Inner conductor Ø (audio) [mm] : | 1,78 |
| AWG (audio) : | 13 |
| Copper strands (audio) : | 78 |
| Copper strand Ø (audio) [mm] : | 0,20 |
| Conductor insulation Ø [mm] : | 3,05 |
| Weight per 1 m [g] : | 163 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 0,8 |
| Style variant : | round |
| Packing : | bulk stock |
| Temperature min. [°C] : | -25 |
| Temperature max. [°C] : | 70 |
| Width [mm] : | 9 |
| Height [mm] : | 9 |

Electrical Data

| | |
|--|-------|
| Insulation resist. per 1 km [GΩ] : | 0,005 |
| Insulation resist. per 1 km (audio) [GΩ] : | 0,005 |
| Conductor resistance per 1 km [Ω] : | 7,7 |
| Test voltage [V] : | 2000 |