

Speaker Cable Elephant SPM460 CPR; 4 x 6,00 mm²; FRNC Ø 13,20 mm; black; Cca

Art. No.: 490-0051-460FC

ANALOG **FRNC** **HALOGEN-FREE** **OFC**



General Data

Article number :	490-0051-460FC
Name :	Elephant SPM460 CPR
EAN :	4049371407021
Properties :	Halogen-free / LSZH
Properties :	FRNC flame retardant
Properties :	OFC oxygen free copper
Properties :	Analog
Application area :	ELA 100 V
Application area :	Installation
Application area :	Studio / Broadcast
Application area :	Mobile outdoor / indoor
Application area :	Stage / live
Application :	Speaker Cable
Colour :	black
BPVo-Euroclass :	Cca

Technical Data

Construction :	(4LIY6,0mm ²)Y
Jacket material :	FRNC
Jacket Ø [mm] :	13,20
Number of Channels (audio) :	1
Inner conductor (audio) :	4
Inner conductor (audio) [mm ²] :	6,00
AWG (audio) :	10
Copper strands (audio) :	84
Copper strand Ø (audio) [mm] :	0,30
Conductor insulation Ø [mm] :	3,05
Weight per 1 m [g] :	353
UV-resistant :	yes
Fire load per m [kWh] :	1,4
Style variant :	round
Packing :	bulk stock
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	13,2
Height [mm] :	13,2

Electrical Data

Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	3,3
Test voltage [V] :	2000
Available since :	V07.0