


Instrument Cable Tricone® MKII; 1 x 0,22 mm²; PVC Ø 5,90 mm; black Art. No.: 300-0021NE

ANALOG

OFC



General Data

Article number :	300-0021NE
Name :	Tricone® MKII
EAN :	4049371002141
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Installation
Application :	Instrument Cable
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	asymmetrical
Construction :	LI2Y(LS)DY1x0,22mm ²
Jacket material :	PVC
Jacket Ø [mm] :	5,90
Number of Channels (audio) :	1
Inner conductor (audio) :	1
Inner conductor (audio) [mm ²] :	0,22
Inner conductor Ø (audio) [mm] :	0,53
AWG (audio) :	24
Shielding :	Copper spiral shielding + semiconductor
Shielding factor [%] :	100
Copper strands (audio) :	28
Copper strand Ø (audio) [mm] :	0,10
Conductor insulation material :	Foam / Skin-PE
Conductor insulation Ø [mm] :	1,80
Weight per 1 m [g] :	42
UV-resistant :	yes
Fire load per m [kWh] :	0,26
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	60
Width [mm] :	5,9
Height [mm] :	5,9

Electrical Data

Capac. cond./shield. per 1 m (audio) [pF] :	85
Insulation resist. per 1 km [GΩ] :	1

Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	90